

SPECIFICATIONS

ALL ELECTRIC

MODEL	2148*	3158*	4208*	4308*	108*
Gallonge*	2 GPM	3 GPM	3.5 GPM	3.5 GPM	100 GPH
Pressure	1400 PSI	1500 PSI	2000 PSI	3000 PSI	400 PSI
Pump	Duplex, Oil Bath Crankcase, Positive Displacement	Triplex, Oil Bath Crankcase, Positive Displacement	Triplex, Oil Bath Crankcase, Positive Displacement	Triplex, Oil Bath Crankcase, Positive Displacement	Triplex, Oil Bath Crankcase, Positive Displacement
Motor	2 HP	3 HP	5 HP	7.5 HP	3/4 HP
Water Heater	Replaceable, 3 - 10,000 Watt, Stainless Steel Immersion Heater, Temperature Control - Standard	Replaceable, 6 - 10,000 Watt, Stainless Steel Immersion Heater, Temperature Control - Standard	Replaceable, 6 - 10,000 Watt, Stainless Steel Immersion Heater, Temperature Control - Standard	Replaceable, 6 - 10,000 Watt, Stainless Steel Immersion Heater, Temperature Control - Standard	Replaceable, 6 - 10,000 Watt, Stainless Steel Immersion Heater, Temperature Control - Standard
Power Requirements	240 V, 3 HP (80 Amps)	240 V, 3 HP (155 Amps) 480 V, 3 HP (77 Amps)	240 V, 3 HP (155 Amps) 480 V, 3 HP (77 Amps)	240 V, 3 HP (160 Amps) 480 V, 3 HP (80 Amps)	240 V, 3 HP (155 Amps) 480 V, 3 HP (77 Amps)
Heat Rise	110° F	140° F	100° F	100° F	250° F
Wand	Trigger-Standard	Trigger-Standard	Trigger-Standard	Trigger-Standard	Open-Standard
Hose	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'	3/8" x 50'
Chemical	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered
Float Tank	Stainless Steel Float Controlled	Stainless Steel Float Controlled	Stainless Steel Float Controlled	Stainless Steel Float Controlled	Stainless Steel Float Controlled
Steam Capacity	N/A	N/A	N/A	N/A	100 GPH
Options	Wheel Kit	Wheel Kit	Wheel Kit	Wheel Kit	Wheel Kit
Dimensions	34" L, 24" W, 37" H	34" L, 24" W, 37" H	34" L, 24" W, 37" H	34" L, 24" W, 37" H	34" L, 24" W, 37" H
Weight	335 LBS	375 LBS	375 LBS	385 LBS	360 LBS

FEATURES

- Triplex, oil bath crankcase pump
- Stainless steel immersion heaters
- Standard temperature control
- 240 volt or 480 volt power, 3 phase power
- 1000 PSI to 3000 PSI
- Heavy duty wheel kit (*optional*)
- Easy grip gun trigger

ADVANTAGES

- Completely powered by electricity
- Safe where open flame is a problem
- Takes up little space
- Creates minimal noise
- Does not emit smoke
- Operates without fumes of any kind

*Gallonge and pressure may vary \pm 5% due to manufacturing tolerances in components. Specifications subject to change without notice.

ENGLISH TO METRIC CONVERSION CHART

1 gallon/minute = 3.78 liters/minute
 1 horsepower = .746 kilowatts
 100 PSI = 7.03 Kg/cm²
 1 foot = .3048 meters
 1 inch = 2.54 centimeters
 1 pound = .45359 kilograms



OLD VALUES. NEW IDEAS.

Alcester, South Dakota 57001
 1.800.255.6823 www.alkota.com



All Electric



OLD VALUES. NEW IDEAS.



A clean running
pressure washer
providing powerful,
environmentally
safe operation.