

XTREME PERFORMANCE PRESSURE WASHER SERIES

# XTREME



# XTREME PERFORMANCE PRESSURE WASHER SERIES



**BUILT AND DESIGNED FOR THOSE WHO DEMAND THE HIGHEST PERFORMANCE. THE XTREME SERIES COMBINES THE DESIGN & ENGINEERING, HIGHEST QUALITY MATERIALS, AND UNCOMPROMISING CRAFTSMANSHIP TO CREATE A PRESSURE WASHER THAT TAKES EVERY STANDARD OF THE INDUSTRY AND BLASTS IT OUT OF THE WATER!**

**STANDARD FEATURES:**

- Pressure atomizing burner coupled with a cold water wrap coil and schedule 80 steel pipe for a long lasting, highly efficient heating system
- Oil bath type pumps designed for rugged use and long life
- Precise chemical metering
- Stainless steel float tank
- Rotary electrical switches
- Enclosed stainless steel control panel
- High quality single phase motor with dual capacitors
- Ball bearing pneumatic wheels
- Easy access fuel tank with replaceable filter
- Safety relief valve
- Heavy steel and stainless steel construction
- 50 ft. of wire braid hose and trigger wand
- Fuel solenoid for positive oil shut off
- Temperature control - variable from 32° to 200°

MODEL	2162AE-X	2162-X	3112-X	3202-X	4182-X	4302-X	5182-X
<b>CAPACITY*</b>	2.1 GPM	2.1 GPM	3 GPM	3 GPM	4 GPM	4 GPM	4.8 GPM
<b>PRESSURE*</b>	1600 PSI	1600 PSI	1100 PSI	2000 PSI	1800 PSI	3000 PSI	1800 PSI
<b>PUMP</b>	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath
<b>MOTOR**</b>	2.3 HP, 115 V, 1 PH	2.3 HP, 115 V, 1 PH	2.3 HP, 115 V, 1 PH	4 HP, 230 V, 1 PH	5 HP, 230 V, 1 PH	8 HP, 230 V, 1 PH	6 HP, 230 V, 1 PH
<b>COIL*** (STEEL PIPE)</b>	95', 1/2" ID Schedule 80	126', 1/2" ID Schedule 80	126', 1/2" ID Schedule 80	126', 1/2" ID Schedule 80	170', 1/2" ID Schedule 80	170', 1/2" ID Schedule 80	170', 1/2" ID Schedule 80
<b>BURNER, PRESSURE ATOMIZING AUTO IGNITION</b>	Kero, #1 Dsl 170,000 BTU	Kero, #1 Dsl 200,000 BTU	Kero, #1 Dsl 315,000 BTU	Kero, #1 Dsl 315,000 BTU	Kero, #1 Dsl 434,000 BTU	Kero, #1 Dsl 434,000 BTU	Kero, #1 Dsl 560,000 BTU
<b>FUEL CONSUMPTION TANK CAPACITY</b>	1.22 GPH 6 GAL	1.4 GPH 12 GAL	2.25 GPH 12 GAL	2.25 GPH 12 GAL	3.1 GPH 14 GAL	3.1 GPH 14 GAL	4.0 GPH 14 GAL
<b>CHEMICAL</b>	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered
<b>FLOAT TANK</b>	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
<b>TEMPERATURE CONTROL &amp; SOLENOID</b>	Standard	Standard	Standard	Standard	Standard	Standard	Standard
<b>STEAM CAPACITY (OPTIONAL)</b>	N/A	60 GPH	90 GPH	90 GPH	120 GPH	120 GPH	150 GPH
<b>WHEELS</b>	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic
<b>DIMENSIONS</b>	L-30 1/2" H-33" W-25"	L-34" H-42" W-27 1/2"	L-34" H-42" W-27 1/2"	L-34" H-42" W-27 1/2"	L-35" H-45" W-29 1/2"	L-35" H-45" W-29 1/2"	L-35" H-46 1/2" W-29 1/2"
<b>WEIGHT</b>	340 LBS	400 LBS	400 LBS	420 LBS	450 LBS	590 LBS	575 LBS

NOTE: All 115 VOLT models have ground fault interrupters standard. Available UL approved.  
 \*Gallage and pressure may vary + or - 5% due to manufacturing tolerances in components.  
 \*\*Special voltages upon request. Gallonages and pressures may be less on 3 phase current.  
 \*\*\*ASTM A-53 steel pipe, spiral wound, cold water wrap design, removable.

**ENGLISH TO METRIC CONVERSION CHART**

1 gallon/minute = 3.78 liters/minute  
 1 foot = .3048 meters  
 1 horsepower = .746 kilowatts  
 1 inch = 2.54 centimeters  
 100 PSI = 7.03 Kg/cm<sup>2</sup>  
 1 pound = .45359 kilograms

2.1 GPM TO 4.8 GPM  
 1600 PSI TO 3000 PSI



Model # XP-03-03. Printed in the U.S.A.

1.800.255.6823 www.alkota.com