



Sahara HD TurboDryer®

When you need maximum power

Get the CFM and static pressure needed to power through specialty drying challenges. This durable and reliable performer works especially well in applications that require stronger static pressure – such as drying in walls, under cabinets and in crawlspaces.



Product Features

- Underside drying vent
- Built-in Microban® antimicrobial product protection to inhibit the growth of odor and stain causing bacteria, mold and mildew in this machine.
- Quick disassembly for cleaning
- Easy-grip handle
- Stackable for storage

Item #F352
\$475 Suggested List U.S. Funds

Product Specifications

Model	F352
Dimensions (H × W × D)	18.8 × 17 × 18.3 in. 47.8 × 43 × 47 cm
Weight	36 lbs. 16 kg
Motor	1 HP
Speeds	Three
Power	10 amps
Switch	Recessed rotary
Rated Airflow	3500 CFM 5947 CMH
Tested Velocity	3206 FT/MIN 977 M/MIN
Airflow per amp	145 CFM
Tested airflow per 15 amp circuit	1454 CFM
Static pressure	2.75 in. 6.9 cm
Cord length	25 ft. 7.6 m
Operating positions	Three (0°, 45° and 90°)
Stackable	Yes
Housing	Rotomolded polyethylene
Safety	UL, C-UL Listed
Issued/Pending Patents: May be covered by	US7,785,064 and/or CA2,571,766

